



Clean Fuel & Lubricant Solutions

Filters • Filter Heads • Manifolds • Kits • Fuel Carts • hP Filters and Heads • DEF • TRAP • Accessories



Why Filter Fuels & Lubricants?

Today's sophisticated equipment, such as diesel engines with increased injection pressures, requires higher cleanliness levels than ever before. Donaldson bulk filtration systems save on costly component replacement, prevent unplanned downtime and prevent a decrease in fuel efficiency due to injector wear. In short, **Donaldson reduces your total cost of ownership**. Learn more about all things related to diesel fuel at MyCleanDiesel.com.

MyClean**DIESEL**.com



Table of Contents

3	Why Do I Need Clean Fuel?
4	What is Clean Fuel?
6	How Do I Get Clean Fuel?
8	Clean Diesel Kits
9	Clean Diesel Carts
10	Fuel and Lubricants Filters
12	Filter Heads
14	Manifolds
16	Bulk hP Filters and Heads
18	Clean DEF Filter
20	T.R.A.P. [™] Breather
22	Reservoir Air Dryer
24	Accessories
26	System Sizing and Design
30	Filter Flow Rates and Pressure Drops



**DIESEL IS
DIRTY.**



**DIRT IS
BAD.**



**REMOVE THE DIRT.
ACHIEVE
MORE.**

As diesel travels from refinery to terminal locations to local bulk storage and finally to your bulk tank, it picks up contamination that is **deadly to today's engines.**

Your local distributor likely delivers diesel that meets or exceeds fuel-industry standards for cleanliness. This is **not clean enough** for your equipment.

By filtering dirt, water and other contaminants before your fuel ever touches your equipment, you'll eliminate costly downtime, **Keep Running** and **Achieve More.**

GET A CLEAN SOLUTION.

To ensure that you're pumping clean, dry fuel into your equipment, call or email a Donaldson Clean Solutions expert. No matter where you are or the size of your operation, there's a Clean Solution that will help you Achieve More.





Achieving the Target Cleanliness of a Fluid


ISO 4406 contamination codes are a way to express fluid cleanliness. The three numbers correspond to the number of particles 4 microns and larger, 6 microns and larger, and 14 microns and larger present in the fluid. This page illustrates what it means to start with a contamination of ISO 22/21/18 and target a cleanliness of ISO 14/13/11.

ISO 4406 CONTAMINATION CODES


Range of number of particles per 100 milliliters

CODE	MORE THAN	UP TO & INCLUDING
24	8,000,000	16,000,000
23	4,000,000	8,000,000
22	2,000,000	4,000,000
21	1,000,000	2,000,000
20	500,000	1,000,000
19	250,000	500,000
18	130,000	250,000
17	64,000	130,000
16	32,000	64,000
15	16,000	32,000
14	8,000	16,000
13	4,000	8,000
12	2,000	4,000
11	1,000	2,000
10	500	1,000
9	250	500
8	130	250
7	64	130
6	32	64
5	16	32
4	8	16
3	4	8
2	2	4
1	1	2

RECOMMENDED ISO CLEANLINESS RATINGS




ISO 22/21/18
Typical cleanliness as fluid goes into your equipment



ISO 14/13/11
Target rating for diesel fuel




ISO 16/14/11
Target rating for hydraulic/transmission oils




ISO 18/16/13
Target rating for heavy gear/engine oils


ISO
22 / 21 / 18



ISO
14 / 13 / 11



SIZES OF FAMILIAR PARTICLES IN MICRONS



100 µm	Grain of Table Salt
80 µm	Human Hair
40 µm	Lower Limit of Visibility
25 µm	White Blood Cell
10 µm	Talcum Powder
8 µm	Red Blood Cell
2 µm	Bacteria
<.5 µm	Silt

Donaldson Delivers Water Protection

Are your bulk fluids passing large amounts of free water downstream – contaminating vehicles and equipment?

Donaldson's water absorbing filter with super absorbent polymer media, DBB0248, will stop flow if large amounts of free water are detected in your ethanol-free fluids. Designing systems with water absorbing filters requires careful sizing considerations. A Donaldson specialist will assist in configuring a system that meets your specific needs for flow and pressure drop.



Choosing the Ideal Filters for Your System Doesn't Need to be Complicated

- 1 Select the **right filter** to achieve **targeted ISO cleanliness**. Proper design of the system will help avoid unnecessary costs.
- 2 Determine the **working pressure** of the system and select the filter line compatible with that pressure.
- 3 Different **types of fluids** have different properties. **Fluid viscosity** plays an important role in restricting the flow through filters. Select a filter that has compatible media-to-fluid properties and will maintain adequate flow and avoid excessive pressure drops. See pages 30-31 for filter flow rates and pressure drops.

Donaldson Delivers Superior Bulk Fluid Filtration

Lower Total Cost of Ownership
Avoid Unplanned Downtime
Maximize Fuel Efficiency
Low Installation Costs
Custom Designs

Modular Solutions
Compact Installation
Low Inventory Costs
Easily Shipped
Easily Serviced



Clean.

Donaldson single-pass filtration on the inlet removes contamination before it can enter your storage tank and contaminate it.


Compact and easy to replace, Donaldson filters are an important line of defense in maintaining fluid quality and can be configured for high flow rates while minimizing pressure drop.



Protect.

Water absorbing filters, T.R.A.P.™ Breathers and Reservoir Air Dryers reduce the risk of moisture and contaminants entering a bulk storage tank so fluids are kept clean and dry. Used together, they'll help guard fluids from free water, airborne contamination and microbial growth for as long as they stay in storage.





Polish.

Unstable fluids and the tank itself can be a source of contamination. Final filtration on the outlet with Donaldson filters ensures that targeted ISO cleanliness levels are achieved before fluids are pumped into your system.

Achieve More.



Clean Diesel Kits

Donaldson Clean Diesel Kits provide simple, effective outlet filtration on fuel dispensers to allow you to pump clean fuel into your vehicles and equipment.

These kits are easy to install on any fuel dispenser and come with everything needed to filter out even the finest contaminants before they can enter your equipment's fuel system. With the included easy-to-follow, step-by-step instructions, you'll have effective, efficient filtration in minutes.



COMPACT X011745

Parallel Filtration

For flow rates up to
32 GPM / 121 LPM

The Compact Clean Diesel Kit is designed for use on mobile service trucks, slip tanks, D-tanks, inside fuel dispensers and other tight locations.



HIGH-CAPACITY X011450

Parallel Filtration

For flow rates up to
125 GPM / 473 LPM

The High Capacity Clean Diesel Kit includes a dual head with two identical filters plumbed in parallel to accommodate higher flow rates and usage volumes.



STANDARD X011448

Parallel Filtration

For flow rates up to
65 GPM / 246 LPM

The Standard Clean Diesel Kit is perfect for smaller operations that need clean fuel delivered efficiently in any environment.



CLEAN AND DRY X011449

Series Filtration

For flow rates up to
50 GPM / 189 LPM

The Clean and Dry Diesel Kit removes fuel contamination, stops water and provides extra protection for your fuel in storage with the T.R.A.P.™ Breather.

See page 13 for Parallel and Series Filtration Flow Paths



The Donaldson diesel filter cart X770816 provides a convenient portable mode of off-line filtration, flushing and fluid transfer. Use it with your in-plant machinery and mobile equipment to achieve and maintain proper ISO cleanliness levels.

In-series pressure filter can provide fine particle removal and a water absorbing element to obtain particulate and water removal. The powerful 50 lpm pump provides efficient fluid transfer and filtration.

The Donaldson diesel filter cart is designed with performance, convenience and safety in mind. Its value added features make it the best choice to protect your machinery and equipment from breakdowns caused by contamination and water.



Supply	220 V @ 50/60 HZ
Electric motor	Built-in thermal lockout
Electric cable	5 m
Maximum fluid viscosity	150 cSt
Flow rate	50 lpm
Maximum Pressure	5 bar (internal bypass)
Indicators	Dual electrical indicators with flashing on the dashboard + manometer for pump pressure
Suction hose	3 m
Discharge hose	4 m
Dirt filtration	P568666
Water adsorption	P570248
Optional	Suction anti-drain valve

Cart	Code	Media	Efficiency	Target	Description
Diesel filter cart X770816	P568666	DERT	4 µm @ β 2000	14/13/11	Specific multi-layer media for Diesel Fuel
	P570248	SAP	95%	150PPM	Cellulose media with adsorbing polymer

Fuel and Lubricants Filters

Donaldson Clean Solutions filters provide unsurpassed cleanliness in a single pass. They are perfect for inlet and outlet filtration applications. Their spin-on design enables fast and simple filter changes without special tools and provides greater protection from contamination during service than traditional cartridge style filters.

These filters incorporate our best technology and construction to handle all fuels and lubricants in all as operating environments. Donaldson Electrostatic Reduction Technology (DERT) prevents filter media damage from electrostatic discharge. Epoxy is used in filter construction for increased fluid compatibility. E-coating provides maximum corrosion resistance and epoxy adhesion. Viton® O-rings provide reliable sealing and maximum fluid compatibility.

Viton® is a registered trademark of E.I. DuPont de Nemours and Company.




FEATURES

- Highly efficient, state-of-the-art filter media and design
- Unsurpassed filter efficiency
- Cleans to target ISO cleanliness in a single pass
- Modular design can be configured for virtually any flow rate or usage level
- Fast and easy to service

APPLICATIONS

- Single pass filtration for clean fluid transfers
- High efficiency kidney looping
- Inlet and outlet filtration at bulk storage tanks
- Dispenser “polishing” filtration on fuel pumps and hose reels
- Mobile and stationary applications



Filter media damage from Electrostatic Discharge (ESD).

D.E.R.T.™

Donaldson Electrostatic Reduction Technology

Electrostatic discharge can be created when diesel fuel or light oils pass through filter media at high flow rates.

The fluid being filtered may have inadequate conductivity to dissipate the charge generated by high flow filtration applications. The electrical charge can build-up in the fluid until it discharges or sparks across the filter, burning holes in the filter media and letting through harmful contaminants.

Donaldson’s proprietary Electrostatic Reduction Technology neutralizes electrical charge and prevents damage to the filter media. This enables efficient single pass fuel filtration in high flow applications.



Part Number	DBB5333	DBB7733	DBB8666	DBB8777	DBB8665	DBB8664	DBB0248
Target ISO Cleanliness*	14/13/11 or better	16/14/11	14/13/11 or better	16/14/11	16/14/11	18/16/13	Not Applicable
Efficiency	4 micron @ Beta 2000	7 micron @ Beta 2000	4 micron @ Beta 2000	7 micron @ Beta 2000		25 micron @ Beta 2000	Not Applicable
Fluid Compatibility	All diesel fuels				Transmission and hydraulic oil	Engine and gear oil	Ethanol-free fluids
Recommended Viscosity Range	<100 cSt				<500 cSt	<6000 cSt	<1500 cSt
Working Pressure	350 psi / 2413 kPa / 24.1 bar						
Element Collapse Pressure	150 psi / 1034 kPa / 10.3 bar						
Rated Static Burst	800 psi / 5516 kPa / 55.2 bar						
Max. Flow Range**	32 gpm / 121 lpm			65 gpm / 246 lpm			
D.E.R.T.***	Yes				No		
Nominal Dimensions	5" x 7.5" / 12.7 cm x 19.1 cm			5" x 14.25" / 12.7 cm x 36.2 cm			
Operating Temperature	-40 to 245 °F / -40 to 118 °C				-40 to 190 °F / -40 to 88 °C	-40 to 245 °F / -40 to 118 °C	

*Select the proper filter by fluid type and OE recommended ISO code. Do not over-filter fluids. Doing so may result in the stripping of beneficial additive.

**Actual flow rate varies based on fluid viscosity, pumping pressure and filter loading.

***DERT™ Donaldson Electrostatic Reduction Technology prevents media damage during high flow fuel applications.

See pressure drop/flow rate charts on page 30-31.



Filter Heads

Clean Solutions filter heads feature robust, aluminum construction with steel inserts to minimize metal-to-metal galling between the head and the filter, even when used with diesel fuel.

The threaded insert contains an O-ring seal to completely seal the clean side of the filter from the dirty side for maximum protection. Viton® seals are compatible with a wide range of fluids and maintain their integrity in cold weather.

For maximum cleanliness, use Clean Solutions filter heads with Clean Solutions filters.

Viton® is a registered trademark of E.I. DuPont de Nemours and Company.



FEATURES

- Steel inserts are safe to use with diesel fuel
- Threads contain an O-ring to completely seal the clean side from the dirty side of the filter
- Heads are pre-ported for optional pressure gauges and service indicators

APPLICATIONS

- For use with Clean Solutions filters
- Compatible with all diesel fuels and lubricants



Single Filter Head



Single Filter Head 1/4" NPTF



Dual Filter Head



 	Part Number	P570329	P570330	P568583
	Connection	SAE-20 O-ring	1/4" NPTF	1 1/2" SAE 4-Bolt Code 61 Flange
	Filter Quantity*	1	1	2
	Max. Flow Range**	65 gpm / 246 lpm		125 gpm / 473 lpm
	Fluid Compatibility	All diesel fuels and lubricants		
	Working Pressure	350 psi / 2413 kPa / 24.1 bar		
	Rated Static Burst	800 psi / 5516 kPa / 55.2 bar		
	Operating Temperature	-40 to 245 °F / -40 to 118 °C		
	Indicator Port	Use to adapt pressure gauges or sampling ports (sold separately)		
	Materials	Aluminum head with threaded steel inserts and Viton® seals		
Compatible Filters	DBB8664, DBB8665, DBB8666, DBB5333, DBB0248, DBB8777, DBB7733			

*Filters sold separately


**Actual flow rate varies based on fluid viscosity, pumping pressure and filter loading.




Single Filter Head
P570329 | P570330




Dual Filter Head
P568583




Single Head Flow Path



Dual Head With Parallel Flow Path



2 Single Heads in Series Remove Dirt First, Then Water



Manifolds

Clean Solutions Filter Manifolds expand capacity or increase flow rate beyond the capability of a single or dual filter head. Two or more manifolds can be plumbed together to accommodate even larger flow rates.

Manifolds split flow evenly between the individual filters. Fluid passes through only one of the filters on its way across the manifold. Dividing the flow between multiple filters plumbed in parallel reduces the pressure drop through each filter.

The combination of Clean Solutions manifolds and filters ensure that your equipment receives the cleanest possible fuel and oil.



4 Filter Manifold



8 Filter Manifold



10 Filter Manifold



Inline 8 Manifold*



Inline 12 Manifold*

	Part Number	P561880	P568932	P568933	1KDFF1008	1KDFF1012
	Filter Quantity**	4	8	10	Up to 8	Up to 12
	Mounting Connection	2" ANSI 150 Flange	4" ANSI 150 Flange			
	Max. Flow Range***	250 gpm / 946 lpm	500 gpm / 1893 lpm	600 gpm / 2271 lpm	400gpm / 1500 lpm	700 gpm / 2650 lpm
	Shipping Weight	140 lbs / 64 kg	310 lbs / 141 kg	390 lbs / 177 kg	66 lbs / 30 kg	128 lbs / 58 kg
	Pressure Gauges	2 pcs 0-160 psi / 0-11 bar gauges included			Accessories Sold Separately	
	Sampling	Includes up-stream and down-stream mini-mess sampling ports with M16 x 2 thread				
	Fluid Compatibility	All diesel fuels and lubricants				
	Working Pressure	ANSI B16.5 flange rating 290 psi / 1999 kPa / 20.0 bar up to 100 °F / 38 °C			145 psi / 1000 kPa / 10 bar	150 psi / 1034 kPa / 10.3 bar
	Construction	Painted carbon steel pipe with aluminum heads			No external aluminum	
Compatible Filters	DBB8664, DBB8665, DBB8666, DBB8777, DBB0248					
Operating Temperature	-40 to 245 °F / -40 to 118 °C					

**Inline 8 Manifolds are available upon request.*

***Filters sold separately*

****Actual flow rate varies based on fluid viscosity, pumping pressure and filter loading.*

FEATURES



- Fast, easy and safe to service
- Requires no electrical or air hook-ups
- Large capacity in small footprint
- Flexible mounting options (horizontal or vertical)
- Cost effective high capacity system

APPLICATIONS


- Bulk fuel and lubricant filtration and water removal
- High flow transfer into or out of tanks and dispensing equipment
- Hard-to-filter high viscosity oils
- Inline industrial filtration of gear oils and lubricants
- Kidney loop applications




4 Filter Manifold
P561880




8 Filter Manifold
P568932



10 Filter Manifold
P568933



Inline 12 Manifold
DFF1012



Bulk hP Filters and Heads

Filtering oil prior to dispensing into equipment is critical to meet the ISO cleanliness specifications demanded by today's OEM's. Donaldson Bulk hP filters provide high efficiency filtration in a single pass.

Service shops use high pressure pumps to force oil through long lengths of piping and hose reels prior to dispensing into equipment. Donaldson Bulk hP filters remove contaminants delivered in oil and picked up in storage or delivery lines during final transfer. They ensure the required ISO cleanliness level is met every time.




hP Single Head


hP Head with Bypass

	Part Number	P566023	P566024
	Working Pressure	1000 psi / 6894 kPa / 68.9 bar	
	Indicator	Yes	
	Bypass Valve	No	Yes - 50 psi / 345 kPa / 3.4 bar
	Connections	SAE-16 O-ring	


Bulk hP Filter


Bulk hP Filter


Bulk hP Filter

	Part Number	P565184	P565185	P565183
	Target ISO Cleanliness	14/13/11	16/14/11	18/16/13
	Fluid Compatibility	Petroleum based oils		
	Max. Flow Range	50 gpm / 189 lpm		
	Efficiency	4 micron @ Beta 2000	8 micron @ Beta 2000	14 micron @ Beta 2000
	Working Pressure	1000 psi / 6894 kPa / 68.9 bar		
	Element Collapse Pressure	300 psi / 2068 kPa / 20.7 bar		
	Application	Hydraulic, gear, transmission and engine oils		
	Rated Static Burst	2200 psi / 15,168 kPa / 151.7 bar		

FEATURES



- Up to 1000 psi / 6894 kPa / 68.9 bar working pressure
- Extended life filters with high dirt holding capacity
- Easy disposal with recyclable can and incinerable element
- Compact design requires only 1.5" / 38 mm clearance for servicing

APPLICATIONS

- Lube shops
- Mobile service trucks
- Other higher pressure single pass applications




Bulk hP Filter Heads
P566023 | P566024



See pressure drop / flow rate curves on page 31.



Bulk hP Filters
P565184 | P565185 | P565183



WARNING


THERMAL EXPANSION Donaldson highly advises following the pump manufacturer's relief recommendations. Pump manufacturers offer relief valves to protect against over pressurization. A mere 10 °F / 5.5 °C increase in oil temp can add 450 psi / 3103 kPa / 31 bar to the system while the pump is shut off.



Clean DEF Filter

Today's Selective Catalytic Reduction (SCR) emissions control systems require clean Diesel Exhaust Fluid (DEF) for precise dosing and complete atomization to occur. However, contamination from transfer and storage or corrosion from incompatible materials can prevent your SCR system from getting the clean DEF it needs for proper operation.

The Donaldson DEF filter catches contaminants before they reach your vehicle or equipment and the onboard DEF filter. Clean DEF ensures proper function of the SCR and extends the life of the onboard DEF filter.



DEF must be clean for proper dosing to occur and turn NOx from exhaust into harmless nitrogen and water vapor.

DEF Filter

FEATURES

- 1 micron at beta 5000 efficiency
- 316 stainless steel housing
- Precise knife edge internal seal
- Heavy duty construction
- Maximum working pressure of 300 psi
- Leak-free O-ring seal
- Integrated gauge/sample ports
- Replacement filters available individually

APPLICATIONS

- DEF dispensers up to 10 GPM




DEF Filter Housing (Choice of Connection)	P575057 1" NPT P575058 1" BSPT Both models include mounting bracket and filter wrench
DEF Filter Element	P575059 sold separately
DEF Housing O-ring	P575060 replacement part
Efficiency	1 micron @ Beta 5000 (99.98%)
Max. Flow Range	10 gpm / 38 lpm
Working Pressure	300 psi / 2068 kPa / 20.7 bar
Operating Temperature	12 to 122 °F / -11 to 50 C°
Housing Construction	316 stainless, EPR O-ring
Filter Material	Polypropylene, EPDM gaskets
Indicator Port	¼" NPT, upstream and downstream
Drain Plug	¼" NPT




PART NUMBERS

- P575057 DEF Filter Housing 1" NPT
- P575058 DEF Filter Housing 1" BSPT
- P575059 Clean DEF Filter
- P575060 DEF Housing Replacement O-ring

MOUNTING BRACKET



DEF Filter Housing
P575075 | P575058



Stainless steel pressure gauge not included – must be sourced separately.

CAUTION

DEF IS HIGHLY CORROSIVE. All pipe fittings must be compatible with DEF. Most plastics as well as stainless steel are acceptable. Carbon steel, zinc, aluminum, brass, copper, etc. are not recommended due to undesirable chemical reactions. If any of these materials are used in your system they should be immediately replaced with a compatible material.

T.R.A.P.™ Breather

The Thermally Reactive Advanced Protection (T.R.A.P.) Breather assembly protects the fluids in your storage tank from airborne particulate moisture contamination and ambient moisture.

It combines a high capacity 3 micron air filter with a deliquescent breather that dries itself when air is expelled from the tank. This self-regenerating capability of T.R.A.P. enables extended life and functionality.

Keep your fluids clean and dry with a Donaldson T.R.A.P. Breather.




Tanks sizes above 10,000 gal. / 37,854 l. may require multiple units and pressure vacuum relief valves.

Contact Donaldson for assistance.



**T.R.A.P.
Breather**





Assembly Part Number	DFF0078
Efficiency	97% efficient @ 3 microns
Max. Flow Range	Combined inlet and outlet flow up to 400 gpm / 1500 lpm maximum
Overflow Check Valve	Opens at 10 mbar / 4" H ₂ O
Operating Temperature	-40 to 200 °F / -40 to 93 °C
Fluid Compatibility	Safe for use with all fuels and lubricants
Indicator	Standard mechanical
Height	16" / 410 mm
Construction	ABS housing, Urethane end caps
Connection	1½" NPT female
Replacement filter	P923075 spin on

FEATURES


- High efficiency air filtration
- Longer life and lower airflow restriction than typical silica gel breathers
- Self-regenerating moisture adsorption
- Easy to service

APPLICATIONS

- For use with all diesel fuels and lubricants
- Above and below ground tanks
- Mobile service trucks
- Indoor or outdoor applications
- Most tanks up to 10,000 gal. / 37,854 liters (large tanks may require multiple units)



T.R.A.P. Breather
DFF0078



WARNING

Always locate your tank's name plate and cross check against the flow chart above to ensure safety. Use maximum flow INTO tank for validating pressure rating and flow OUT OF tank for vacuum ratings. **DO NOT EXCEED TANK PRESSURE OR VACUUM.**




Reservoir Air Dryer

The Donaldson Reservoir Air Dryer eliminates the need to continually replace conventional desiccant breathers, enhancing reservoir breathing systems by continuously purging and dehydrating reservoir headspace.

With no electrical requirements, the Donaldson Reservoir Air Dryer combats ambient ingress of moisture by introducing a steady stream of clean, dry air to the reservoir. This constant airflow helps sustain optimal conditions and prevents the formation of condensation and rust in the reservoir, minimizing the potential for particulate and water ingress through reservoir access points.

When combined with a T.R.A.P. Breather, the complete system keeps moisture and contamination out, even if fluid flow rate out of the tank surpasses the Reservoir Air Dryer flow rate into the tank.



Reservoir Air Dryer

Assembly Part Number	P575852
Efficiency	Reduces dew point as much as 150 °F (83 °C)
Outlet Flow Volume @ 100 psi and dew point suppression	0.5 scfm (14.2 slpm) maximum
Inlet Air required @ 100 psi	0.8 scfm (22.7 slpm) maximum
Pre-Filter Condition	Visual Indicator (Green/Red)
Pressure Regulator	Dial Gauge
Coalescer Drain	Automatic Float Type
Max Working Pressure	116 psi (800 kPa / 8.00 bar)
Max Operating Temperature	125°F (52°C)
Fluid Compatibility	Petroleum and Phosphate Ester Fluids, Diesel Fuels*
Inlet/Outlet Connection	¼" NPT
Mounting Bracket	3/8" - 16 UN Threaded Nut
Weight	<5 lbs (<3 kgs)
Replacement	Coalescing Pre-Filter

**The Reservoir Air Dryer is not recommended for use on gasoline holding tanks or for the head space of any flammable liquid (Flash Point of 100F/38C)*



FEATURES

- The clean, dry air sweep dehydrates the reservoir headspace and removes dissolved moisture from exposed oils and fuels*
- Operates with standard plant air; instrument quality air is not required.
- Submicron coalescing air filter collects oil and water droplets and fine particles from inlet air
- Automatic drain purges captured liquid with no intervention required
- Visual indicator monitors filter condition
- Membrane air dryer reduces plant air dew point by as much as 150 °F (83 °C)
- Pressure regulator depressurizes the air and ensures that the proper flow rate of air is introduced into the reservoir

APPLICATIONS



- Lubricant system reservoirs
- Diesel storage tanks
- Oil storage tanks
- Gear boxes
- Hydraulic system reservoirs



**The Reservoir Air Dryer is not recommended for use on gasoline holding tanks or for the head space of any flammable liquid (Flash Point of 100F/38C)*



Reservoir Air Vent
P575852



Accessories

PARTS

Part Number	Description	Application
1KDF1005	I-12 Blanking Cap	Blank off up to 6 orifices on I-12 manifold for flush mounting
P563107	4-Bolt Code 61 Flange to 1½" NPT Adapter	Adapts P568583 Dual Head to 1½" NPT
P573642	Threaded Pipe Nipple	1¼" NPT, for connecting two P570330 single heads in series
P164050	Threaded Insert O-rings	Replacement O-rings for heads and manifolds, Viton, not for use on hP
P564669	ABS Breather, 3 Micron	Small oil tanks under 250 gal. / 1000 liters, 1" NPT, splash containment for mobile applications

PRESSURE GAUGES AND SERVICE INDICATORS

Part Number	Description	Application
P574967	Electrical Service Indicator 50 psi / 345 kPa / 3.45 bar	Use with all Clean Solutions heads and manifolds, microprocessor compatible
P574177	Visual Service Indicator 50 psi / 345 kPa / 3.45 bar	For single heads and hP heads, industrial grade green to red
P165965	Visual Service Indicator 25 psi / 172 kPa / 1.72 bar	For single heads and hP heads, industrial grade green to red
P573682	Upstream Pressure Gauge Adapter	For single and dual heads, ⅛" NPT
P573681	Pressure Gauge, 0 – 60 psi / 414 kPa / 4.1 bar	For single and dual heads, ⅛" NPT, center back mount, 1½" diameter, use with P573682 adapter
P563296	Pressure Gauge, 0-100 psi / 689 kPa / 6.89 bar	For single and dual heads, ⅛" NPT, center back mount, 2" diameter, use with P573682 adapter
P563809	Direct Gauge Adapter	For Clean Solutions manifolds, M16 x 2 to ¼" NPT adapter, use to mount pressure gauge to test point
P562709	Pressure Gauge, 0-160 psi / 1103 kPa / 11.0 bar	For Clean Solutions manifolds, stem mount, 2½" diameter, use with P563809 adapter

SAMPLING TOOLS

Part Number	Description	Application
P573414	Upstream Sampling Port Adapter	For single, dual heads, and hP heads, SAE-4, use with P563224 for sampling
P573415	Upstream Indicator Port Adapter	For single, dual heads, and hP heads, SAE-4, use with P563224 for sampling
P563212	Test Point Heads and Manifolds	For all Clean Solutions manifolds, 1/8" NPT to M16 x 2
P563224	Test Point	For all Clean Solutions heads and manifolds, SAE-4 to M16 x 2, use with P573414 and P573415 adapters
P563250	Test Point Hose Assembly, 12"	1620 series M16 x 2 thread, for use with P563212 and P563224 mini mess test points
P563252	Test Point Hose Assembly, 24"	1620 series M16 x 2 thread, for use with P563212 and P563224 mini mess test points

TEST KIT

Part Number	Description	Application
X009329	Patch Test Kit	Test kit for measuring fluid cleanliness
P567969	0.8 Micron Membrane Filter	Spares for Patch Test Kit, purchase in multiples of 100
P567868	5.0 Micron Membrane Filter	Spares for Patch Test Kit, purchase in multiples of 100
P567865	Analysis Cards	Spares for Patch Test Kit, purchase in multiples of 50
P567861	120 ml Sample Bottle	Spare for Patch Test Kit

Accessories vary by geographical region. Consult your local Donaldson representative for more information.



The Importance of Temperature in Sizing Your Filtration System

Fluid viscosity, measured in centistokes (cSt) or Saybolt Seconds Universal (SSU or SUS), is the resistance of a fluid to flow (thickness of fluid). Low viscosity fluids pass through filters with less resistance than high viscosity fluids. Higher fluid viscosities have higher pressure drops due to higher resistance passing through the media.

The colder the fluid, the higher the viscosity, so the lowest potential temperature of the fluid during filtration is the best measure for sizing a bulk filtration system. Due to the high specific heat capacity of fluids, the lowest ambient temperature may not be an accurate reflection of the actual fluid temperature. Avoid oversizing your system by using the stored fluid temperature and not the lowest ambient temperature, which tends to be lower than the temperature of the fluid in storage or transport.



WATER **HONEY**

Temperature greatly impacts fluid viscosity. Consider that ISO 32 oil at 104 °F / 40 °C has the same viscosity as diesel fuel (similar to water). When temperatures drop to -4 °F / -20 °C, the viscosity of that ISO 32 oil increases dramatically to over 2,000 centistokes, which is similar to honey at room temperature.


FUEL/OIL KINEMATIC VISCOSITY COMBINED WITH TEMPERATURE IN CENTISTOKES CST

SAE Gear Oil			75W			80W	85W	90			140		
SAE Engine Oil			5W	10W		20		30	40	50			
ISO Grade			15	22	32	46	68	100	150	220	320	460	680
°F	°C	Diesel											
248	120				4	4	6	7	9	12	13	18	23
230	110				4	6	7	9	12	15	19	24	30
212	100		1	5	5	7	9	11	15	19	25	32	41
194	90		3	5	7	9	11	15	20	26	34	44	58
176	80		5	7	9	11	15	20	27	36	48	63	85
158	70		6	9	11	15	20	28	39	52	71	95	130
140	60		8	12	15	21	29	40	57	80	110	151	211
122	50		11	15	22	30	43	62	99	128	181	254	365
104	40	1	15	22	32	46	68	100	150	220	320	460	680
86	30	2	21	32	51	76	116	175	271	409	613	907	1,380
68	20	3	33	51	87	135	214	334	536	838	1,290	1,980	3,130
50	10	4	52	87	162	264	438	711	1,190	1,920	3,070	4,870	8,020
32	0	5	85	180	340	585	1,020	1,720	2,990	5,060	8,400	13,900	23,900
14	-10	9	185	375	820	1,500	2,770	4,880	8,890	15,700	27,200	47,000	85,000
-4	-20	15	400	800	2,350	4,650	91,20	16,800	32,300	60,000			

Bulk filtration systems must be designed properly to meet the desired ISO cleanliness code while maintaining the existing flow rates. The filter type and quantity of filters varies based on the desired cleanliness, system pressure and flow rate.

Increasing the **flow rate** will increase the pressure drop across a filter. If the pressure drop is too high, system flow rate can be reduced or damage to the filter can occur. To reduce the pressure drop, increase the number of filters in the system.

The chart below demonstrates the **pressure drop** experienced by a filter with various viscosities and flow rates. The steeper the pressure drop curve, the more filters that must be added to the system. Additional filters plumbed in parallel will decrease the flow rate per filter, lowering the pressure drop and allowing existing flow rates to be maintained.





Steps to Sizing a Bulk Application

1 Define product flow rate, fluid type and pressure drop restriction. New systems should ideally have less than 15 psi / 1 bar pressure drop.

2 Use the table on the page 26 to determine fluid viscosity using the fluid type and temperature.


INFORMATION GATHERING

FLOW RATE: _____

FLUID TYPE: _____


PRESSURE DROP: _____

TEMPERATURE: _____






3 Select the appropriate filter based on desired ISO cleanliness code and working pressure (see pages 10 and 11).



4 Determine the filter pressure drop using the flow rate and the fluid viscosity according to the appropriate chart on pages 30 – 31. Add the manifold pressure drop using the flow rate on page 15 to calculate total pressure drop.



You Don't Need To Do It Alone.

Let a Donaldson specialist assist you by providing recommendations on sizing, selection and positioning of Donaldson filters. You can help us design your system by providing:

Responses to steps 1-4 above.

A schematic of your fluid transfer process (hand sketches work great), and/or

Photographs of your site (tanks, inlets and outlets).

Contact your Donaldson representative.


Divide total pressure drop through one filter by the desired system pressure drop. This number is equal to the amount of filter required to clean the fluid properly at the determined flow rate. If the pressure drop is more than 15 psi / 1 bar, go up one size.

$$\frac{\text{CALCULATED PRESSURE DROP}}{\text{DESIRED PRESSURE DROP}} = \text{[Two Filter Icons]}$$


Flow Rates and Pressure Drops

FUEL AND WATER ABSORBING FILTERS


DBB5333 - Compact Fuel Filter




DBB8666 - Fuel Filter




DBB7733 - Compact Winter Fuel Filter



DBB8777 - Winter Fuel Filter








DBB0248 - Water Absorbing Filter



Flow Rates and Pressure Drops

LUBRICANT FILTERS





Global Presence with a Local Touch

At Donaldson, we've built a strong, flexible and responsive distribution network to serve our customers around the world.

Localized Manufacturing – It starts with 30+ manufacturing locations around the world – producing most filters in the regions where they're used.

Primary Distribution Centers – Filters then move to our regional warehouses and distribution center hubs – meaning the filters you need are never far away.

Logistics – We work with a network of transportation and logistics companies, consolidators and cross-docking facilities to deliver products to distribution partners quickly and efficiently.

Distribution Partners – We've built one of the largest, strongest and most responsive distributor networks in the filter industry – meaning you can find the filters and support you need, nearly anywhere in the world.



Donaldson Europe

Interleuvenlaan 1
B-3001 Leuven

MyCleanDiesel.com
donaldson.com

Need a Clean Solution?

As a global organization, we have offices throughout the world. Please direct your inquiry to clean.solutions@donaldson.com. This will enable us to address your inquiry in the shortest possible time.

Mexico	Brazil	South East Asia	Korea
Latin America	Europe & Middle East	Greater China	Australia
Caribbean	South Africa	Japan	India

Brochure No. F111500 ENG-EU (8/15)

© 2015 Donaldson Company, Inc. All rights reserved. Donaldson Company, Inc. reserves the right to change or discontinue any model or specification at any time and without notice.